

PURION Electric Control Cabinet - Model 2

....is characterized by compact construction design. The construction follows laws, standards and regulations.



The PURION Electric Control Cabinet - Model 2 can be optionally delivered made from steel, stainless steel or plastic material

The protective system is IP 54.

The power supply is carried out with $3^{\sim}/N/PE^*$ 50Hz 400/230V.

The Electric Control Cabinet can equipped with the PURION Operating Time Counter (OTC2) or the PURION Operating Power Detection (OPD2).

The potential free contact D1-D2 (error amount signaling) enables easy integration into existing remote monitoring systems.

Additionally it is possible to equip the PURION Electric Control Cabinat with a main alert function.

manufacturer	PURION [®] GmbH
type	Electric Control Cabinet Model 2
dimensions (L x B x H mm)	800 x 1000 x 300
protective system	IP 54
configuration	 lamps for function control main switch earth leakage circuit breaker (ELCB) 4-pole (30mA) fuse potential free contact D1-D2 (external over current protection necessary)
electrical connection	3 ~/N/PE* 50 Hz 400/230V
weight	approx. 65 Kg
total power	up to 12 x 106W (depending on no. of UV Plants)
over current protection	3 x 6A or 3 x 10A
options	 Operating Time Counter (OTC2) Operating Power Detection (OPD2)

This Electric Control Cabinet is applied at:

applications with multiple UV Plants (up to 16 UV Plants):

- PURION products for treatment of water
- PURION UV-Sets
- AIRPURION

industrial applications

applications with very small space for installations

Advantages

- space saving management of several PURION UV Plants via central control cabinet
- individual configuration possible (e.g. earth leakage circuit breaker, time relay, etc.).

info@purion.eu www.purion.eu

- construction also possible with stainless steel or plastic material

with earth leakage circuit breaker 4-pole